

22AWG 4 CONDUCTOR FIRE ALARM CABLE (FPLR-RISER) UNSHIELDED




DESCRIPTION

Fire Alarm Cable, 22/4, Solid, Unshielded,
FPLR (Riser), 500ft Spool

FEATURES

- Fire Alarm Cable
- 22AWG 4 Conductor Bare Copper
- FPLR (Power-Limited Fire Alarm Riser Cable)
- Fire protective signal circuit
- Applications: Smoke alarms and detectors, pull boxes, burglar alarms, addressable fire alarm systems
- ETL Listed, RoHS Compliant
- Spool Dimensions: 5.5"x6.5"x6.5"
- 500ft Spool



SKU: 315-224/R/5RD

Conductor

Material 22AWG Solid Bare Copper
Conductors 4 Conductor

Insulation

Thickness (mm) PVC 0.165
Colors Red, Green, Yellow, Black
Rip Cord Nylon Rip Cord

Jacket

Thickness (mm) PVC 0.45
Overall Diameter (mm) 3.10
Color Red

Mechanical Characteristics

Test Object	Jacket
Test Material	PVC
Before Aging	
Tensile Strength (Mpa)	>=13.8
Elongation (%)	>=100
Aging Condition (°Cxhrs)	100x168
After Aging	
Tensile Strength (Mpa)	>=85% of unaged
Elongation (%)	>=50% of unaged
Cold Bend(-20±2°Cx4hrs)	No crack

Jacket Print

VERTICAL 4001453 cETLus CMR/FPLR 22AWG 4C SOLID 75C FIRE ALARM
CABLE RoHS V1379PXXXX [XXXXFT]

VERTICAL CABLE

951.696.7772 California

800.749.2447 Florida

845.391.8318 New York



www.verticalcable.com

Rev. 05/2017

Specs subject to change without notice.

It is the sole responsibility of the user to have the most current specs.