© VERTICAL CABLE Simply Connect.

DESCRIPTION

Category-3, UTP, 24awg 8 Conductor Solid-Bare Copper, Lose-Twist.

FEATURES

- Suitable for Communication Applications
- Suitable for Telephony and Security Systems
- Category-3 Unshielded Twisted Pair Cable
- 4-Pair Easily Identified Color-Striped Pairs
- AWG24 Solid Bare Copper Conductors
- Excellent Attenuation and Crosstalk
- Exceeds EIA/TIA 568 B.2-1 Standards
- ETL Listed
- Supplied in 1000[°] Pull Boxes



Dimensions 13.5H x 13.5L x 8.5W (inches) 45pcs per pallet (Packaging may vary)

VERTICAL CABLE 954 454-3554 Florida Office 951 696-7772 California Office

CAT3 VOICE GRADE CABLE 4 PAIR UTP (Lose Twist)

SKU: 052 SERIES

Technical Data

Rated Temperature (°C) Rated Voltage (V) Product Standard Certification Conductor Size	70 30 CMR Solid Bare Copper 24 AWG			
Insulation	PE			
Insulation Diameter (±0.005mm)	ter (±0.005mm) 0.88			
Iwisted Pair Diameter (±0.01)	1.76			
Assembly Diameter	S.40 PVC			
Outer Diameter (+0.10mm)	5.00			
Rip Cord	Yes			
Color of Pairs				
Pair A	White-Blue			
Pair B	White-Green			
Pair C	White-Orange			
Pair D	vvnite-Brown			
Mechanical Characteristics				
Test Object	Jacket			
Test Material	PVC			
Before Tensile Strength (Mpa)	>=13.8			
Aging Elongation (%)	>=100			
Aging Condition (°Cxhrs)	100x168			
After Tensile Strength (Mpa)	>=85% of unaged			
Aging Elongation (%)	>=50% of unaged			
Cola Bena (-20±2° CX4nrs)	INO GRACK			

Marking on Jacket

VERTICAL 4001453 ETL VERIFIED CMR FT4 UTP 4PR 24AWG CAT3 TIA/EIA-568B.2 RoHS XXXFT (SEQUENTIAL FOOT MARKERS ON JACKET)

Jacket color available in White and Gray



www.verticalcable.com

Rev. 04/2011 Subject to change without notice.

CAT3 VOICE GRADE CABLE 4 PAIR UTP (Lose Twist)

PERFORMANCE

Electrical Characteristics

Impedance100±15 OhmsD-C Resistance of each Core98 Ohms/Km (Max)The Average of Imbalance of D-C Resistance upon cores ≤2.0%

Frequency	Return Loss	Attenuation	Delay
(Mhz)	(Min dB)	Max (dB/100m)	(ns/100m)
0.772	12	2.2	576
1	12	2.6	570
4	12	5.6	552
8	12	8.5	545
10	12	9.7	545
16	10	13.1	543
Frequency	Next	Skew	
(Mhz)	(Min dB)	ns	
0.772	43.0		
1	41.3		
4	32.3		
8	27.8	45	
10	26.3		
16	23.3		

TECH DRAWING



VERTICAL CABLE

954 454-3554 Florida Office 951 696-7772 California Office

www.verticalcable.com

Rev. 04/2011 Subject to change without notice.