

RG59 95% BC BRAID COAXIAL CABLE (CM)



VERTICAL CABLE
Simply Connect.

DESCRIPTION

RG59 Bare Copper Coaxial Cable with 95% Bare Copper Braid.

FEATURES

- 20AWG Solid Bare Copper Conductor For Optimal Signal Transmission
- 95% Bare Copper Braid Coverage For Optimum Signal Protection
- Indoor Cable Application (non-conduit per NEC) for: CCTV
- RoHS Compliant, ISO9001:2000
- Available in 1000ft Pull Box

SKU: 107-2176/WH

Physical Characteristics:

Conductor

Size	20 AWG
Material	Bare Copper (Solid)
Construction	0.81±0.1mm

Dielectric

Material	Foamed PE
Diameter	3.66±0.10mm
Color	White

Braid

95%x16x8x0.12±0.005mm BC

Jacket


Material	PVC (UL 75 Deg C)
Diameter	6.1±0.10mm
Color	White

Electrical Characteristics

Sparker Test	3000VAC
Impedance	75±3 Ohms
Capacitance	53±3pF/m
Velocity of Propagation	85%
Return Loss	(5~470Mz)≥22dB (470~1000Mz)≥20dB

Mechanical Characteristics

Operating Temp.	-30°C to 75°C
-----------------	---------------



VERTICAL CABLE

954 454-3554 Florida Office
951 696-7772 California Office

www.verticalcable.com

Rev. 02/2011

Subject to change without notice.