

# CAT5 ENHANCED 350MHz UTP - CMR RATED




## DESCRIPTION

Category-5E, 24AWG, UTP, 8C Solid Copper, 350MHz, Riser Rated, PVC Jacket 1,000ft.

## FEATURES

- Category-5E Unshielded Twisted Pair
- 24AWG Solid Bare Copper Conductors
- 350MHz Bandwidth for Data Applications
- Easily Identified Color-Striped Pairs
- Exceeds EIA/TIA 568-C.2, ISO/IEC-11801
- RoHS and TAA Compliant
- ETL Listed
- 1,000ft Pull Box



## SKU: 151 - SERIES

### Technical Data

Product Standard Certification  
NVP

CMR  
67%

### Conductor

Size

**Solid Bare Copper**  
24AWG

### Insulation

Insulation Diameter

**PE**  
0.90 mm (±0.05mm)

### Jacket

Outer Diameter

Rip Cord

**PVC**  
5.2 mm (±0.2mm)  
Yes

### Color of Pairs

Pair 1  
Pair 2  
Pair 3  
Pair 4

Blue, White-Blue  
Orange, White-Orange  
Green, White-Green  
Brown, White-Brown

### Mechanical Properties

Bending Radius:

Operating Temperature:

4XOD (without load)  
-20°C ~ 75°C

### Marking on Jacket

VERTICAL ETL VERIFIED CAT5E TO ANSI/TIA 568-C.2 ETL CMR  
24 AWG 4PR 75C UTP c(ETL)us FT 4 350MHZ RoHS XXXXFT  
(SEQUENTIAL FOOT MARKERS ON JACKET)

Jacket color available in  
Blue, Black, White, Green, Gray, Red, Yellow, Orange, Pink, Purple

**VERTICAL CABLE**

951.696.7772 California  
800.749.2447 Florida  
845.391.8318 New York



[www.verticalcable.com](http://www.verticalcable.com)

Rev. 01/2017

Specs subject to change without notice.

It is the sole responsibility of the user to have the most current specs.

# CAT5 ENHANCED 350MHz UTP - CMR RATED

## PERFORMANCE

### Electrical Properties:

DC resistance:	Max 9.38Ω / 100m at 20°C
Resistance unbalance:	Max 5% at 20°C
Mutual capacitance:	Max 5.6 nf / 100m at 1kHz
Cap. unbalance to ground:	Max 330 pf / 100m at 1kHz
Characteristic impedance:	(100 ± 15) Ω at 1 ~ 100 MHz
Nonimal velocity of propagation:	67%
Propagation delay:	≤ 535 ns / 100m
Delay skew:	≤ 45ns / 100m

Frequency (Mhz)	Return Loss (Min dB)	Attenuation Max	Next (ns/100m)	ACR Typ(db)
1	20.0	2.0	65.3	67.3
4	23.0	4.1	56.3	56.2
8	24.5	5.8	51.8	50.0
10	25.0	6.5	50.3	47.8
16	25.0	8.2	47.3	44.0
20	25.0	9.3	45.8	41.5
25	24.3	10.4	44.3	38.9
31.25	23.6	11.7	42.9	36.2
62.5	21.5	17.0	38.4	27.4
100	20.1	22.0	35.3	19.3
200	18.0	32.4	30.8	3.5
300	16.8	41.0	28.2	-----
350	16.3	44.9	27.2	-----

Frequency (Mhz)	PSNext (Min dB)	ELFEXT Min(db/100m)	PSELFEXT Min(db/100m)
1	62.3	63.8	60.8
4	53.3	51.7	48.7
8	48.8	45.7	42.7
10	47.3	43.8	40.8
16	44.3	39.7	36.7
20	42.8	37.7	34.7
25	41.3	35.8	32.8
31.25	39.9	33.9	30.9
62.5	35.4	27.8	24.8
100	32.3	23.8	20.8
200	27.8	17.7	14.7
300	25.2	14.2	11.2
350	24.2	12.9	9.9

**VERTICAL CABLE**

951.696.7772 California

800.749.2447 Florida

845.391.8318 New York



[www.verticalcable.com](http://www.verticalcable.com)

Rev. 01/2017

Specs subject to change without notice.

It is the sole responsibility of the user to have the most current specs.