
® VERTICAL CABLE Simply Connect.

DESCRIPTION

16/2 Stranded Bare Copper Conductors, Unshielded with an overall jacket. Plenum Rated, 500ft Pull Box

FEATURES

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Supplied in a 500ft Pull Box



16AWG 2 CONDUCTOR PLENUM RATED

SKU: 211-162/P/5BK

Conductor

Material Size Stranding

Conductors

Insulation

Material Thickness Colors Ripcord

Jacket

Material Thickness Overall Diameter Color Bare Copper 16AWG 19 Strand (19x0.0113in., 19x0.287mm) 2 Conductor

PL-PVC 0.075 in. (1.9mm) Nominal Black, Red Yes

PL-PVC 0.0181 in. (0.46mm) Nominal 0.186 in. (4.72mm) Nominal Black

Electrical Properties

Temp. Rating DCR Conductor -20°C ~ +75°C 13.7 Ohms/Km. @ 20°C

Ratings/Approvals

NEC Article 800, UL Subject 444, CMP/CL2P (UL), RoHS Compliant

VERTICAL CABLE 951.696.7772 California

800.749.2447 Florida 845.391.8318 New York



www.verticalcable.com Rev. 01/2017

Specs subject to change without notice. It is the sole responsibility of the user to have the most current specs.