

FIBER OPTIC PATCH CORD

Multimode Duplex



DESCRIPTION

Duplex Multimode Fiber Optic Patch Cord, LC, SC or ST Connectors, PC Polish, 10G, UL

FEATURES

- Multimode Duplex Fiber Optic Patch Cord
- LC-LC, LC-SC, LC-ST, SC-ST, ST-ST connector configurations available
- 1m/2m/3m/5m/7m/10m/15m lengths available
- Available in standard or custom configurations
- 3.0mm diameter
- Category OM1 (62.5/125)
- Low back reflection and insertion loss
- PVC jacket
- Ceramic ferrule
- UL, RoHS Compliant



SKU: 261 Series

Technical Data

Fiber Type	62.5/125 μ m
Polish	PC
Buffer	Kevlar
Overall Diameter	900 μ m
Jacket	PVC (OFNR-Rated)
Overall Diameter	3.0mm
Mechanical Characteristics	
Attenuation @ 850nm	3.75dB/km
Attenuation @ 1310nm	1.5dB/km
Typical Insertion Loss	\leq 0.20dB
Max Insertion Loss	\leq 0.30dB
Min Bandwidth @ 850nm	160kHz/km
Min Bandwidth @ 1310nm	500kHz/km
Maximum Tensile Load	100N/cm

Jacket Print

OPTICAL CABLE 62.5/125 MM-2.8x5.7 OFNR RoHS UL
(Cord Length Label attached)

VERTICAL CABLE

951.696.7772 California
800.749.2447 Florida
845.391.8318 New York



www.verticalcable.com

Rev. 02/2015

Specs subject to change without notice.

It is the sole responsibility of the user to have the most current specs.