

14AWG 2 CONDUCTOR FIRE ALARM CABLE (FPLP-PLENUM) SHIELDED




MADE IN USA

DESCRIPTION

Fire Alarm Cable, 14/2, Solid, Shielded, FPLP (Plenum), 1000ft Spool

FEATURES

- Fire Alarm Cable
- FPLP (Power-Limited Fire Alarm Plenum Cable)
- Fire protective signal circuit
- Applications: Smoke alarms and detectors, pull boxes, burglar alarms, addressable fire alarm systems
- 14AWG 2 Conductor
- 100% Solid Bare Copper Conductors
- Shielded
- MADE IN USA
- ETL Listed, RoHS Compliant
- Spool Dimensions: 12'H x 12'D
- 1000ft Spool



SKU: 315-142/S/P/RD

Conductor

Material 14AWG Solid Bare Copper
Conductors 2 Conductor

Insulation

Thickness (mm) 0.031
Colors Red, Black

Rip Cord Shield Drain

Polyester Rip Cord
Aluminum/Mylar
24 AWG Soolid Tinned Copper

Jacket

Thickness (mm) 0.381
Overall Diameter (mm) 5.21
Color Red

Electrical & Physical Properties

Operating Temperature Rating (°C) -20°C to +60°C
Operating Voltage Rating (V RMS) 300
Resistance @20°C (Ω/1000ft) 2.526
Weight (lb/1000ft) 43

Ratings/Approvals

NEC Article 760, NFPA 262 Steiner Tunnel Smoke and Flame Test, UL 1424, Type FPLP, ETL Listed, RoHS Compliant
Does not comply with NYC LL5 (Local Law 5)

Jacket Print

14 AWG 2C SHIELDED PLENUM FIRE ALARM CABLE (ETL)_{us} TYPE FPLP
FILE NUMBER MADE IN USA [JULIAN DATE/YR][LOT#](XXXFT)

MADE IN USA



VERTICAL CABLE

951.696.7772 California
800.749.2447 Florida
845.391.8318 New York

www.verticalcable.com

Rev. 05/2017

Specs subject to change without notice.

It is the sole responsibility of the user to have the most current specs.