

CAT6 DATA JACK 90° DEGREE STYLE



DESCRIPTION

Category-6 Data Grade Keystone Jack 90°
Degree 8x8 Conductors

FEATURES

- Available in various colors for easy identification
- 110-IDC Contacts (Terminal Block)
- Color Coded for 568A and 568B standards
- ANSI/TIA-568-C.2
- ISO/IEC11801 2nd edition EN50173 2nd edition
- Compatible with the I-Punch Tool
- Narrow connector allows high port density in small areas
- UL Listed, ETL Listed, RoHS Compliant



Available in
Black, Blue, Green, Gray, Ivory,
Yellow, Red, White, Orange

SKU: 302-SERIES

Physical Specifications

| | |
|-------------------------|------------------------------------|
| Dimension (mm) | 19.86H x 17W x 31D |
| Housing Material | |
| Housing | UL 94V-0 self extinguished plastic |
| IDC Housing | UL 94V-0 self extinguished plastic |
| Contact Material | |
| IDC 110 Contacts | Phospor bronze, nickel plated |
| Nose Contacts | 50µ Gold plating over nickel |
| Operating Life | Minimum 750 Insertions |
| Compability | 22 to 26 AWG Solid |
| PCB | FR-4, 1.6mm double sided |
| Cap | UL 94V-0 rated |

Product Certifications

ANSI/TIA-568-C.2, FCC, 3P
ETL Listed

Electrical:

| | |
|-----------------------|-------------------------|
| Current Rating | 1.5Amp Max |
| Dielectric strength | 1000V RMS for 1min |
| Insulation resistance | 500mΩ |
| Contact resistance | 20mΩ |
| DC resistance | 0.1 Ohm |
| Temperature Range | -10°C to 60°C max |
| Humidity | 10%~90%; non condensing |



Compatible with the I-Punch Tool
Sku# 078-2150

VERTICAL CABLE

800.749.2447 Florida
951.696.7772 California
845.391.8318 New York



www.verticalcable.com

Rev. 04/2015

Specs subject to change without notice.
It is the sole responsibility of the user to have the most current specs.