

DESCRIPTION

Category 3 Voice Grade Keystone Jack. 8 Position 6 Conductors.

FEATURES

- USOC Wire Configuration
- 110-IDC Contacts (Terminal Block)
- ANSI/TIA-568-C.2, ETL/UL Listed
- Fits on Standard Keystone ports
- Compatible with the I-Punch Termination tool
- Narrow housing allows high port density in smaller areas.



Available in Almond, Ivory and White

CAT3 VOICE GRADE JACK KEYSTONE STYLE

SKU: 350-SERIES

Physical Specifications

Dimension (mm) 19.75H x 17W x 31.1D

Housing Material

Housing ABS+PC UL 94V-0 IDC Housing PC UL 94V-0

Contact Material

IDC 110 ContactsPhospor bronze, Tin platedPlug Contacts50 micro-inch Gold platedOperating LifeMinimum 750 InsertionsCompability22 to 26 AWG Solid

 PCB
 FR-4, UL 94V-0

 Cap
 ABS+PC UL 94V-0

Product Certifications

ANSI/TIA-568-C.2 UL / ETL Listed

Performance:

Insertion Force: 20N max. (IEC 606037-4)
Retention Strenght: 7.7 kg between jack and plug
Operating Temp: -10°C to 60°C max















VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York