18AWG 2 CONDUCTORFIRE ALARM CABLE (UNSHIELDED)






DESCRIPTION

Fire Alarm Cable, 18/2, Solid, Unshielded, FPLR (Riser), 1000ft Spool, Red

FEATURES

- Fire Alarm Cable
- FPLR (Power-Limited Fire Alarm Riser Cable)
- Fire protective signal circuit
- Applications: Smoke alarms and detectors, pull boxes, burglar alarms, addressable fire alarm systems
- 18AWG 2 Conductor
- 100% Solid Bare Copper Conductors
- Unshielded
- MADE IN USA
- ETL Listed, RoHS Compliant
- Spool Dimensions: 6'H x 12'D
- 1000ft Spool



SKU: 315-182/R/RD

Conductor

Material Bare Copper Size 18AWG Stranding Solid

Conductors 2 Conductor

Insulation SR-PVC

Thickness 0.009 in. (0.2286mm)

Nominal

Colors Red, Black

JacketPolyvinyl Chloride (PVC)Thickness0.015 in. (0.381mm) NominalOverall Diameter0.147 in. (3.7338mm) Nominal

Color Red

Electrical & Physical Properties

Capacitance 30.7 pF / ft Nom. Impedance 60 Ohms Vel of Prop 55%

Resistance 6.385 Ohms D.C. Per 1000ft @68°F

Ratings/Approvals

NEC Article 760, ETL, Type FPLR, CMR, RoHS Compliant.





VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York